



# Reliable Pumps

## Bumper Pulled Hydrostatic Test Pump



## Features

- RD 30 Triplex Pump
- Inline Fluid end design for pressures from 3000 to 22500 psi
- Flow rates from 4 to 14 gpm
- Relief valve, safety rupture disc and pressure gauge are standard
- Diesel engine
- 230 gallon water tank
- Hose storage reel with 400' capacity available upon request
- 100' of high pressure hose up to 22,500 psi available upon request
- Conveniently mounted control panel
- Remote PTO Control Lever
- Heavy duty reinforced skid
- Simple, safe one man operation

RD 30 Series 2.25" Stroke

Max. Plunger Load 6200 LB.			Flow				
Max Pressure			200 RPM	300 RPM	400 RPM	500 RPM	600 RPM
Plunger Dia.	PSI	BAR	GPM/LPM	GPM/LPM	GPM/LPM	GPM/LPM	GPM/LPM
.625" - 15.87MM	20,000	1379	1.79/6.7	2.69/10.1	3.59/13.5	4.48/16.9	5.37/20.3
.630" - 16MM	20,000	1379	1.80/6.81	2.73/10.3	3.64/13.7	4.55/17.2	5.46/20.6
.750" - 19.0MM	15,000	1034	2.58/9.7	3.87/14.6	5.16/19.5	6.45/24.4	7.74/29.3
.875" - 22.2MM	10,000	690	3.51/13.3	5.27/19.9	7.03/26.6	8.78/33.2	10.53/29.8
1.000" - 25.4MM	8,000	552	4.58/17.3	6.88/26	9.17/34.7	11.47/43.4	13.76/52

**RELIABLE PUMPS CONSULTANTS**

5404 Cedar Crest, Houston, Texas 77087 Ph: 713-640-2718 Fax: 713-640-1604 Web: [reliablepumps.com](http://reliablepumps.com)