

SUBSEA FLUSHING UNIT



FEATURES

THE RPC FLUSHING UNIT HAS 3 MAIN ELECTRICAL SAFETY FEATURES

1. LOW FLUID LEVEL WITH INDICATOR LIGHT, ALARM, AND SHUTDOWN.
2. FLUID TEMPERATURE SENSOR WITH INDICATOR LIGHT, ALARM, AND SHUTDOWN.
3. THE THIRD IS BLOWN RUPTURE DISK SENSOR WITH INDICATOR LIGHT, ALARM, AND SHUTDOWN. IF ANY ALARM HAS BEEN TRIPPED THE MACHINE WILL NOT TURN BACK ON UNTIL IT HAS BEEN TAKEN CARE OF.

THE HIGH FLOW CAPABILITY WITH VARIABLE FLOW DISPLACEMENT ALLOWS THE OPERATOR TO REMOVE PARTICLES WITH HIGH REYNOLDS NUMBER CONSIDERATION THROUGH DIFFERENT SIZE HOSES AND TUBING WITHOUT HAVING TO BYPASS ANY FLUID TO GENERATE HEAT. EACH UNIT IS EQUIPPED WITH A KIDNEY-LOOP PROCESS TO CLEAN FLUID ENTERING THE STATIONS AS WELL AS RETURNING.



PUMP INFO

RD30 SERIES 2.25" STROKE

MAX. PLUNGER LOAD 6200 LB.			FLOW					
	MAX PRESSURE		200 RPM		300 RPM		400 RPM	
PLUNGER DIA.	PSI	BAR	GPM	LPM	GPM	LPM	GPM	LPM
.625" - 15.87MM	16,000	1,100.8	1.79	6.7	2.69	10.1	3.59	13.5

WWW.RELIABLEPUMPS.COM/INFO@RELIABLEPUMPS.COM

5404 CEDAR CREST
HOUSTON, TEXAS 77087
UNITED STATES
PHONE: 713 640 2718
TOLL FREE: 800 801 6993
FAX: 713 640 1404



RELIABLE PUMPS CONSULTANTS

SUBSEA FLUSHING UNIT



- A. HIGH PRESSURE PUMP WITH VARIABLE CAPACITY
0-60 GPM WITH PRESSURES RANGING FROM 500 TO
20,000 PSI
- B. TEFC OR EXPLOSION PROOF
- C. MULTI STAGE FILTRATION
- D. INLAND OR OFFSHORE DESIGN
- E. STAINLESS STEEL RESERVOIR TANK
- F. CHART RECORDER

MULTI-PORTS OUTLET AND RETURN MANIFOLD
WITH INDIVIDUAL SAMPLING PORTS ALLOW
SEVERAL LINES TO BE FLUSHED AT ONCE TO
REDUCE TIME. WE CAN REDUCE YOUR TIME BY
AS MUCH AS 80%!



WWW.RELIABLEPUMPS.COM/INFO@RELIABLEPUMPS.COM

5404 CEDAR CREST
HOUSTON, TEXAS 77087
UNITED STATES
PHONE: 713 640 2718
TOLL FREE: 800 801 6993
FAX: 713 640 1404



RELIABLE PUMPS CONSULTANTS